# HEURISTIC FOR ASYMMETRIC CAPACITATED VEHICLE ROUTING PROBLEM

by Tjutju Tarliah Dimyati

**Submission date:** 28-May-2021 03:37PM (UTC+0700)

**Submission ID:** 1595899952

File name: 6.\_20120214\_Heuristic\_For\_Asymmetric.pdf (11.12M)

Word count: 6622

Character count: 34371



ISSN: 1978-774X



2012

5th International Seminar on Industrial Engineering & Management (5th ISIEM)

"Innovation in technology, information, and management concerning worldwide economic challenge"

February 14-16, 2012 Aston Hotel, Manado, Indonesia

## Organized by:















Sponsored by:





Supported by:



5 ISSN: 1978-774X

# Proceeding

The 5<sup>th</sup> International Seminar on Industrial Engineering and Management (5<sup>th</sup> ISIEM)

Aston Hotel, Manado, Indonesia February 14<sup>th</sup> – 16<sup>th</sup>, 2012

Organized by :

Industrial Engineering Department of













Sponsored by:



Supported by:





#### FOREWORD

This issue is published in line with the Fifth International Seminar on Industrial Engineering and Management (5<sup>th</sup> ISIEM). The theme to this seminar is "Innovation in Inchnology, Information, and Management Concerning Worldwide Economic Challenge". The articles cover a broad spectrum of topics including Quality Engineering and Management, Supply Chain Management, Operation Research, Decision Support System and Artificial Intelligence, Production System, Industrial management, and Ergonomics. The articles provide an overview of critical research issues reflecting past achievements and future challenges.

Full papers were reviewed by peer reviewers and finally we published 80 titles. This issue and seminar become special as more delegates come and join from various country as well as universities. We host 77 delegates both from abroad and local.

First and second ISIEM are hoteled only by three universities, namely Trisakti, Esa Unggul and Gunadarma Universities. This year event, it's hosted by seven universities, i.e. Atma Jaya Catholic University of Indonesia, Trisakti University, Esa Unggul University, Pasundan University, Al-Azhar Indonesia University, Tarumanagara University, and last but not least, De La Salle Manado University

In this occasion, let us give special thank to Mr Marcus Pitt, President Director PT SOHO Industri Pharmasi and Assoc. Prof. Dr. Chuvej Chansa-ngavej, Director, SIU Research Center Program Director - PhD in Management Science, School of Management Shinawatra University (SIU International), Thailand. Your contribution to this seminar as reviewers and as keynote speakers makes this event more valuable. We are also grateful to all reviewers, for their commitment, effort and dedication in undertaking the task of reviewing all of the abstracts and full paper. Without their help and dedication, It would not be possible to produce this proceeding in such a short time frame.

We want to thank all those who submitted papers for review and those whose papers were chosen for presentation at the seminar and those who submitted manuscripts to be published in this proceeding. We highly appreciate all members of committee director, steering committee and organizing committee for mutual efforts and invaluable contributions for the success of the seminar.

Finally, have intensive discussion in this seminar and enjoyable stay in Manado

Vivi Triyanti ST. M.Sc (Atma Jaya Catholic University of Indonesia)

Chair of Committee



#### Steering Committee

- 1. Iphov Kumala Sriwana, ST, M.Si
- 2. Parwadi Moengin, PhD
- 3. Vivi Triyanti, S.T., M.Sc
- 4. Ir. Syarif Hidayat, MM, MEng.Sc
- 5. Dr.Ir. Chevy Herli Sumeri A, MT
- 6. Lamto Widodo ST. MT

(Esa Unggul University)

(Trisakti University) (Atma Jaya Jakarta Catholic University)

(Al Ashar Indonesia University)

(Al Azhar Indonesia University)

(Pasundan University)

(Tarumanagara University)

#### **Organizing Committee**

Chair Vivi Triyanti, ST, M.Sc. (Atma Jaya Jakarta Catholic

University)

Co-Chair Ir. Triwulandari SD, MM (Trisakti University)

Secretary Lamto Widodo ST. MT (Tarumanagara University)
Treasury Iphov Kumala Sriwana, S.T., M.Si (Esa Unggul University)

#### **Proceeding Editor**

Rahmi Maulidya, ST, MT (Trisakti University)

Marcellinus Bachtiar ST., MM

(Atma Jaya Jakarta Catholic University)
Feliks Prasepta, ST., MT.

(Atma Jaya Jakarta Catholic University)

#### Leaflet

Ir. Nofi Erni, M.M. (Esa Unggul University)
Adianto (Tarumangara University)

5

Sponsorship

Rina Fitriana, S.T., M.M. (Trisakti University, INDONESIA)

#### Operational (Preparation for the event)

Nunung Nurhasanah,ST,MT
Ir. Syarif Hidayat, MEng, MM
Lina Gozali
Endro
Riya
(Al Azhar Indonesia University)
(Tarumangara University)
(Tarumangara University)
(Esa Unggul University)

#### Operational (On the event)

Ahmad Juang Pratama, ST., MSc. (Al Azhar Indonesia University) (Al Azhar Indonesia University) Ahmad Chirzun, ST., MT. Ir. Yogi Yogaswara, MT. (Pasundan University) Ir. H. Chevy Herli SA., MT. (Pasundan University) Dr. Ir. Hj. Tjutju T. Dimyati, MSIE. (Pasundan University) Ir. Noldi Watuna, MM (Unika De La Salle Manado) Debby Paseru, ST, MMSI, M.Ed (Unika De La Salle Manado) Ronald Rachmadi, ST, MT (Unika De La Salle Manado) Mario Vitores, ST (Unika De La Salle Manado)

#### Website

Ir. Wahyukaton, MT. (Pasundan University)

The 5<sup>th</sup> International Seminar on Industrial Engineering and Management (5<sup>th</sup> ISIEM)

#### REVIEWER

- 1. Prof. Ir. I Nyoman Pujawan, MEng, PhD
  (Sepuluh Nopember Institute of Technology, INDONESIA)
- 2. Assoc.Prof. Dr. Chuvej Chansa-ngavej
  Director, SIU Research Center, Program Director PhD in Management
  Science, School of Management Shinawatra University (SIU International),
  THAILAND
- 3. Dr. Ferry Jie (RMIT University Melbourne, AUSTRALIA)
- 4. Parwadi Moengin (Trisakti University, INDONESIA)
- 5. Ir. Triwulandari SD, M.M. (*Trisakti University*)
- 6. Dr. Ir. Lily Amelia, M.Agr., M.M. (Esa Unggul University, INDONESIA)
- 7. Ir. Nofi Erni, M.M.
  (Esa Unggul University, INDONESIA)
- 8. Prof. Dr. Hadi Sutanto
  (Atma Jaya Jakarta Catholic University, INDONESIA)
- 9. Prof. Dr. Weggie Ruslan (Atma Jaya Jakarta Catholic University, INDONESIA)
- 10. Prof. Dr. Ir. S. Sardy, M.Eng.Sc (Al Azhar Indonesia University, INDONESIA)
- 11. Dr. Ir. Tjutju Tarliah Dimyati, MSIE (Pasundan University, INDONESIA)
- **12.** Lamto Widodo ST. MT (Tarumanagara University, INDONESIA)

# TABLE OF CONTENT

Foreword Committee Reviewer Table Of Content

# Book One

## IM – Industrial Management

No	Code	Title and Author	Page					
1	R01	Encouraging Business Model Innovation To Improve Firm's Competitiveness Through Deutero-Learning And Adhocracy Culture Jahja Hamdani Widjaja	IM – 1					
2	R05	e-Government: Awareness and Participation Among Malaysian Citizens Sabariyah Binti Din, Lim Ai Ling, Anand Agrawal	IM – 9					
3	R06	Financing Innovation In Indonesia: A Promising Future  Jean-Baptiste Morin	IM – 17					
4	R11	Corporate Environment, Operations Strategy And Company Performance At Garment Industries In West Java Province  **Atty Tri Juniarti**						
5	R15	The Influence of Internal Control Implementation-Based Sarbanes Oxley Act (SOA) Section 404 on The Auditor's Opinion of The Public Company Management  Assertions  Liza Laila Nurwulan, Ika Rachmawati	IM – 29					
6	R21	Formulation Of Strategies To Increase Brand Equity Poke Sushi Restaurant Using le Matrix Rudy Vernando Silalahi, Donny Indrawan, Andy Mitra Gunadi	IM – 40					
7	R25	Developing The Maintenance Scorecard For The Quality Improvement Of Mass Transportation Service (Study at PT Kereta Api Indonesia)  Emelia Sari, Didien Suhardini, Winnie Septiani	IM – 50					
8	R26	Developing Business Process Model To Provide Workers In An Outsourcing Company: A Case Study Triarti Saraswati, Amelia Paramita, Invanos Tertiana	IM – 56					
9	R27	Do we ready to face Globalization of Accounting? Exploratory Study of Accounting Faculties in Indonesia <i>Wirawan ED Radianto</i>	IM – 63					
10	R29	Calibrating Competitive Factors To Define Corporate Strategies: A Case Study <i>Liliani, Michael Siek</i>	IM – 70					
11	R30	The Effect Of Product Value And Store Image Intention To Buy Car (A Case Study Of Visitors In Surabaya OTO Seller)  J.E. Sutanto	IM – 77					
12	R36	Entrepreneurship Education: Enhance Indonesian economic growth and national development <i>Widjaja Hartono</i>	IM – 83					

#### $Table\ of\ Content$

13	R39	Designing CRM Program For Telecommunication Wholesale Business Based On Customer Lifetime Value Analysis Fransiscus Rian Pratikto	IM – 88
14	R40	The Relationship Between Corporate Social Responsibility And Social ROI With Resource-Based View As Moderating Factors: A Conceptual Model <i>Fan Liu, Ronald S.</i>	IM – 96
15	R41	Integration David's Strategic Management Model With Balanced Scorecard Performance Management System  *Triwulandari S. Dewayana, Adi Irianto*	IM – 103
16	R43	Cultural Changing In Global Competition  Meidiahna Kusuma	IM – 111
17	R44	Study Of Airasia; World's Best Low-Cost Airline  Charly Hongdiyanto	IM – 117
18	R55	Performance Evaluation Model Of Lubricant Agencies Using Balance Scorecard, Analytic Hierarchy Process, And Decision Making-Trial Evaluation Laboratory (Case Study In Pertamina Lubricants)  *Dwinta Utari, Fauzia Dianawati, Arief Hariyanto*	IM – 124
19	R56	Relations Model Of Employee Commitment To The Organization Towards Employee Loyalty And Working Quality  Fauzia Dianawati, Dwinta Utari, Hanifah Handayani	IM – 131
20	R58	Analysis Of Asset Ownership And Debt For Jakarta MRT Project In South- North Corridor (Lebak Bulus-Kampung Bandan) Romadhani Ardi, Erlinda Muslim, Dimas Setyo Utomo	IM – 139
21	R65	Computer Integrated Manufacturing Maturity Model Design In Mineral Water Industry  Yudha Prasetyawan, Ria Novitasari	IM – 147
22	R70	Enhancement Fleisch And Osterle Model At PT Garuda Indonesia Base On Virtual Organization Concept Dadan Umar Daihani, Rivan Syamsurijal Biya	IM – 155
23	R71	Developing UKMGoesOnline to be a Virtual Broker in Indonesia by Adopting Vega and Virtec Matric Model Dadan Umar Daihani, I Dewa Made Ari Dananjaya, Arief Dwi Hartanto	IM – 163
24	R73	UST Method As The Effective Strategy In Credit Management Angreine Kewo, Mario Vitores	IM – 170
25	R76	A Dynamic Balanced Scorecard Of An Upstream Oil And Gas Portfolio Company Fransiscus Rian Pratikto, Karlina Eka Wahyuni	IM – 178
26	R77	Indicators For Knowledge Management Performance Measurement From Human Capital Perspective Using Knowledge Management Balanced Scorecard  **Amelia Kurniawati, Luciana Andrawina**	IM – 187
27	R87	Analysis Of Relationship Between Internal Locus Of Control On Career Maturity Among IE Students In University Z Hans Christian Andrew Salim, Marsellinus Bachtiar Wahyu	IM – 193
28	R91	Election Analysis Of Cooperation Using The Analisys Hierarchy Process In The Development Spam Pdam Bandar Lampung City Wiwik Sudarwati	IM – 201
	·	1	L

#### Table of Content

#### 3 SCM – Supply Chain Management

No	Code	Title and Author	Page
1	R33	Scorecard Design For Measuring Company Performance Based On Customer And Suppliers Perspectives Case Study at KF Indonesia Eka Kurnia Asih Pakpahan, Reviandari Rizkiani	SCM - 1
2	R68	Supplier Performance Evaluation Using Data Envelopment Analysis BCC Model and Super Efficiency Model in Pumping Unit Producer Yadrifil, Maya Arlini P., Irmawati Ulfah	SCM - 7
3	R83	A Synchronization Approach for Supply Chain Performance Hedging in Cane Based Agroindustry Iphov K. Sriwana, Taufik Djatna	SCM - 14
4	R86	The Effect Of Buyers' Characteristics On The Selection Of Categories Of Indonesian Domestic Airline Service  Mimi Halimin, Feliks Prasepta S. Surbakti	SCM - 21
5	R90	A Forecasting Model Of Raw Material Supply Using Artificial Neural Network <b>Nofi Erni</b>	SCM - 26

#### 5 ER – Ergonomics

No	Code	Title and Author	Page
1	R22	Ergonomics Intervention Using Cognitive Approach In Reducing Work Error Nataya Charoonsri Rizani, Mithia Ulfa, Winnie Septiani	ER – 1
2	R45	The Influence Of Ergonomic Concept To The Work Posture And The Physical Work Environment And Its Impact On The Worker Performance (A Case Study On The Manufacturing Process Division at PT. Sinar Terang Logamjaya Bandung)  M. Yani Syafei, Erwin Maulana Pribadi	ER – 7
3	R46	Breastfeeding Jacket Design Using Ergonomic Approach  Mira Rahayu, Fajar Dhitya, Grita Adrinovian	ER – 16
4	R57	The Ergonomic Analysis Of Walking Posture Using Student Backpack Maya Arlini Puspasari, Arian Dhini, Komara Jaya	ER – 21
5	R62	Ergonomics Intervention To Reduce Work Load On Wood Department In Furniture Manufacturing  Dian Mardi Safitri, Ni Made Putri Wulandari, Nora Azmi	ER – 27
6	R78	Standard Of Cloth Sizes For Toddler (Girl) Based On Athropometry Dimension Vivi Triyanti, Maria Santiana	ER – 34
7	R88	Workload Evaluation between Beginner and Skillful Worker (Case Study: Manual Harvesting and Transporting of Sugar Cane)  Lamto Widodo, Bambang Pramudya, Sam Herodian, M. Faiz Syu'aib	ER – 40

# Book Two

# S – Production System

		0.1011 0 90.1011	3					
No	Code	Title and Author	Page					
1	R02	Configuration of an Industrial Ethernet Network to Control a Flexible Manufacturing System Joe Kwan Hoei	PS – 1					
2	R35	Batch Scheduling In Two-Stage Flowshop With Common And Dedicated Machine To Minimize Total Actual Flow Time Pratya Poeri Suryadhini	PS – 8					
3	R38	Improvement Of Assembly Line Design In PT. SMI By Lean Manufacturing Approach Sadzwina Faiza Prasasya, Dida Diah Damayanti	PS – 14					
4	R48	Proposal Of Machine Maintenance Planning And Maintenance Information System (Case Study at PT. BBI)  Amal Witonohadi, Dannis S. Pramudya	PS – 21					
5	R49	Evaluation To Production Performance Considering Departments Distance and Route Time Using Simulation With ARENA  Yogi Yogaswara						
6	R52	The Usage Of Lean Manufacturing Concept For Reducing Waste Of Corrugated Box Cardboard Production (Case Study: at Converting Division, PT. Purinusa Eka Persada Bandung)  Resha Akbar, Rd. Rohmat Saedudin, Haris Rachmat	PS – 32					
7	R59	Inventory Control Of The Products For Special Sale Model  Y M Kinley Aritonang, Feronika	PS – 44					
8	R64	Application Synchronous Manufacturing By Using Drum-Buffer-Rope And Promodel Simulation  Tiena Gustina Amran, Annisa Pranowo	PS – 49					
9	R74	Considering The Time Value Of Money Into The Lot Size Decision In Material Requirement Planning  Arum Sari, Ade Agus Junaedi	PS – 57					
10	R75	A Preliminary Study On Safety Stock Placement Problems With Stochastic Lead Times Carles Sitompul, Dedy Suryadi, Johanna Hariandja	PS – 63					
11	R82	Applying Theory Of Constraint And Particle Swarm Optimization Method To Determine The Quantity Of Product Mix Sumiharni Batubara, Rahmi Maulidya, I Komang Mahendradata	PS – 67					
12	R85	Comparison Performance Analysis Between Heuristic Pour, Nawaz Enscore And Ham (NEH) Algorithm In Completing The Flowshop Scheduling At PT. XYZ  Lina Gozali, Lamto Widodo, Teddy Kurniawan	PS – 73					
13	R89	Applying Multi Population Genetic Algorithm to Multi Objective Scheduling System  Rahmi Maulidya, Sumiharni Batubara and Mochammad Iman Fachry	PS – 81					

#### Table of Content

#### 3 QM – Quality Engineering & Management

		<del></del>					
No	Code	Title and Author	Page				
1	R04	Utilization Of Chromium Waste From Tanning Industry as Ceramic Glaze Lusia Permata Sari Hartanti	QM – 1				
2	R07	Quality Improvement Of Packaging Label Printouts: An Analysis And Implementation Of Six Sigma And Work Method Redesign <i>Djoko Sihono Gabriel, Aris Triono</i>	QM – 6				
3	R08	Process Monitoring With Multivariate Control Chart For Auto Correlated Data: A Case Study At Pharmaceutical Industry <i>Ig. Joko Mulyono, Ivan Gunawan, Suhartono</i>	QM – 11				
4	R16	Quality Control Development Based On Lean Six Sigma Method Wahyukaton					
5	R18	Quality Improvement and Jar Cleo Product Development based on Quality Function Deployment at PT Berkah Plastic Industri Johnson Saragih, Dedy Sugiarto, Wira Nurdjana	QM – 21				
6	R50	Longterm Upgrading Airport Runway's: An Approach Of Support Vector Regression  Amar Rachman, Sumarsono Sudarto, Sarah Noviani	QM – 26				
7	R53	Design Of TQM Scorecards For Construction Service Industry Using AHP And Fuzzy-AHP Method Based On Malcolm Baldrige National Quality Award 2009-2010 Criteria  Erlinda Muslim, T. Yuri M. Zagloel, Intan Purbosani	QM – 33				
8	R60	Quality Improvement Of Food Jar Products Using Six Sigma Method Leli Deswindi, Christin	QM – 40				
9	R61	Analysis Of Operational Wastes In A Logistics Service Company Using Lean Six Sigma Method Syarif Hidayat, Lisa Heryani	QM – 48				
10	R63	FMEA (Failure Mode And Effect Analysis), And Expert System In Lubricant Machine Oil Production Process Rina Fitriana, Andhika Mandala Utama, Johnson Saragih	QM – 56				
11	R66	Automated Visual Grading And Inspection For Egg  Yudha Prasetyawan, Achmad Mustakim	QM – 62				
12	R79	Implementation Study Of Malcolm Baldrige Criteria For Performance Excellence (MBCFPE) In Higher Education (Case Study Of University X) <b>Ahmad Chirzun, Adi Pranoto</b>	QM – 70				
13	R84	Customers And Employees Satisfaction Analysis With Human Sigma Approach; A Case Study In A Hotel Service Dendi Prajadhiana Ishak, Triyono	QM – 77				

#### 3 DSS – Decision Support System and Artificial Intelligence

No	Code	Title and Author	Page
1	R14	The Evolution of Computing: from Local Computing to Cloud Computing Maria Angela Kartawidjaja	DSS – 1
2	R19	Design Knowledge Management Model of Standarization Accounting Code System: Study Case Audit Board of Republic of Indonesia Riya Widayanti	DSS - 10

#### $Table\ of\ Content$

3	R24	Proposal For The Design Of Decision Support System For Machine Maintenance Priority In PT. Biuteknika Bina Prima Winnie Septiani, Sucipto Adi Suwiryo, Amalia Nurinsana	DSS – 18
4	R32	Comparison Of Nutritional Status Data Calculation Between K-Nearest Neighbour And Bayesian Algorithms Erni Seniwati, Ferry Wahyu Wibowo	DSS – 24
5	R37	An Architecture for Legal Knowledge-based System in Indonesia Wahyu C. Wibowo, Adriana Sari Aryani	DSS - 31
6	R67	Designing Business Process Model And Data Architecture For Information System At Fitness Center (Case Study Helios Fitness)  Sonna Kristina, Rivans Liviyandi	DSS – 35
7	R81	Quality Improvement of Personal Computers Configuration Management Using IT Infrastructure Library: Study on IT Directorate of XYZ University Ahmad Juang Pratama, Paula Ruth Prawinoto	DSS – 41

#### **OR – Operation Research**

No	Code	Title and Author	Page
1	R23	A Design of Risk Transfer System for Raw Materials Commodity of Agroindustry <i>IGA Anom Yudistira, and Lisa Ratnasari</i>	OR – 1
2	R28	Fuzzy Multi Objective Linear Programming For Optimization Of Agroindustrial Logistic Design <i>Pudji Astuti</i>	OR – 13
3	R34	Heuristic For Asymmetric Capacitated Vehicle Routing Problem <i>Tjutju Tarliah Dimyati</i>	OR – 20
4	R51	Demand Forecasting Comparasion Between Artificial Neural Network And Support Vector Regression With Traditional Methods Sumarsono Sudarto, Amar Rachman, Rendra Satya Wirawan	OR – 27
5	R54	Determination Of Balance Ratio Load Factor And Calculation Of Waiting Time For Urban Transportation In Depok Nunung Nurhasanah, Dewi Wulandari	OR – 33
6	R69	Exponential Barrier Method in Solving Linear Programming Problems <b>Parwadi Moengin</b>	OR – 39
7	R72	Study and Evaluation of Methods for Solving Traveling Salesman Problem (TSP) Interaction Gani Method and Nearest Neighbor Method <i>Mohammad Syarwani</i>	OR – 44

# HEURISTIC FOR ASYMMETRIC CAPACITATED VEHICLE ROUTING PROBLEM

14 Tjutju Tarliah Dimyati

Industrial Engineering Department, Pasundan University tjutjutarliah@ymail.com; adimyati@bdg.centrin.net.id

#### **ABSTRACT**

The vehicle routing problem (VRP) is commonly defined as the problem of designing optimal delivery or collection routes from one or several depots to a set of geographically scattered customers, under a variety of side conditions. This problem is generally described through a graph, whose arcs represent the road sections and vertices correspond to the depot and customer locations. The arcs (and consequently the corresponding graph) can be directed or undirected, depending on whether they can be traversed in only one direction or in both directions. Since each arc is associated with a cost then if the graph is directed, the cost matrix is asymmetric and the corresponding problem is called asymmetric vehicle routing problem (AVRP). Although the symmetric problems are special cases of the asymmetric ones, the latter were much less studied in the literature. In this paper, a type of problem, called the Asymmetric Capacitated Vehicle Routing Problem (ACVRP) is discussed and a heuristic algorithm is proposed to solve the problem.

Keywords: Vehicle Routing, Asymmetric, Capacitated, Heuristic

#### 1. INTRODUCTION

The Vehicle Routing Problem (VRP) has been thoroughly studied in a variety of areas, such as Operation Research, Artificial Intelligence, etc. It can be defined as a problem of finding the optimal routes of delivery or collection from one or several depots to a number of cities or customers, while satisfying some constraints. Collection of household waste, gasoline delivery trucks, goods distribution, and mail delivery are the most used applications of the VRP. Since the VRP plays a vital role in distribution and logistics, thousands of papers have been written on several VRP variants such as Capacitated Vehicle Routing Problem (CVRP), VRP with Time Windows (VRPTW), VRP with Backhauls (VRPB), VRP with Pick-Up and Delivery (VRPPD) and Periodic VRP (PVRP) (Toth. 2000

In the CVRP, all the customers correspond to deliveries and the demand are deterministic and may not be split. The vehicles are identical and based at a single central depot, and only the capacity restrictions for the vehicles are imposed. Typically, the problem objective is to find delivery routes starting and ending at the

depot that minimize a total travel cost or distance without violating the capacity constraints of the vehicles. This type of problem has been studied extensively in the literature. Many exact algorithms, which dominated bv branch-and-cut methods, have been proposed for solving the problem (see (Ralphs, 2003), (Toth, 2002), (Baldacci, 2004), (Lysgaard, 2004), (Fukasawa, 2006)). However, the efficient solution of CVRP is still challenging problem, which requires the use of heuristics to large problems. Fortunately, several families of heuristics have been proposed. They can be broadly classified into two main classes, i.e. classical heuristics and meta-heuristics. The quality of solutions produced by meta-heuristics is much higher than that obtained by classical heuristics, but the price to pay is increased computing time. Some classical heuristics for the problem have been surveyed by (Laporte, 2002), while meta-heuristics have been surveyed by (Gendreau, 2002).

ISSN: 1978-774X

The road network where the movements of the delivery vehicles are performed is represented by a graph with arcs and vertices. Arcs represent roads and vertices correspond to the road



intersections, junctions, customer cations, and the depot. The arcs and its corresponding graph can be directed or undirected, depending on whether they can be traversed in only one direction or in both directions. If the graph is directed, the distance from one point to another in a given space can bo different from the inverse distance. Since each arc is associated with a cost then if the graph is directed, the cost matrix is asymmetric, and the corresponding problem is called Asymmetric Capacitated Vehicle Routing Problem (ACVRP). The scheduling problems with sequence dependent setup time and resource constraints, as well as the problem of distribution in urban areas where distances depend on one-way directions impose on roads, are practical spplications of ACVRP in which the distance matrix associated to customers' set is asymmetric.

Although the symmetric problems are special cases of the asymmetric ones, the latter were much less studied in the literature. Most of the exact and heuristic algorithms from the literature considered only the symmetric and in many cases, only the Euclidean version of the problem. Algorithms for the non-Euclidean CVRP, and especially the Asymmetric CVRP. have been neglected in the literature by comparison with the extensive effort devoted to studying Euclidean VRP. So far, there is only one heuristic (Vigo, 1996) and two exact methods (Fischetti, 1994), (Laporte, 1886) for ACVRP found in the literature. This state of affairs is at odds with the fact that asymmetric models are relevant to a wider range of applications, and more general than symmetric models. Hence it is important to study heuristic methods for ACVRP.

The purpose of this paper is to propose heuristic algorithm developed for ACVRP, although it may also be used for the symmetric instances. The rest of this paper is organized as follows: In section 2 a problem formulation of ACVRP is discussed. Section 3 is devoted to a discussion of the developed heuristic. Section 4 gives a numerical example for the proposed heuristic. The conclusion is put in section 5.

#### 2. FORMULATION OF THE ACVRP

#### Problem Identification

The Asymmetric Capacitated Vehicle Routing Problem (ACVRP) is defined on a complete directed graph G = (V, A) where  $V=\{0,1,2,\ldots,n\}$  is the set of nodes (vertices), 0 is the depot (origin), and the remaining nodes are customers. The set A =  $\{(i, j): i, j \in V, i \neq j\}$  is the set of arcs. Each customer  $i \in V \setminus \{0\}$  is associated with a positive integer demand  $q_i$  and each arc (i, associated with asymmetric deterministic travel cost  $c_{ij}$  (i.e.  $c_{ij} \neq c_{ji}$  in general) which might violate the triangular inequality (i.e.  $c_{ij} \le c_{ik} + c_{kj} \forall i,j,k$ ). In this case, the cost of traveling from node i to node j can be approximated by the distance  $d_{ii}$  with  $d_{ii} \neq d_{ii}$ .

There are *m* vehicles with identical capacity Q. The ACVRP consists of determining a set of m vehicle routes satisfying the following conditions:

- Each route starts and ends at the
- Each customer is served exactly by one vehicle.
- The total demand of each route does not exceed the vehicle capacity Q.
- The total cost of all routes is minimized. Because of the problem objective and in or ensure feasibility, it is assumed that the number of available vehicles m is equal to the minimum number of vehicles sufficient to serve all the customers. Mathematically, the minimum number of vehicles needed to serve all customers can be stated as:

$$m = \begin{bmatrix} \sum_{i \in V} q_i \\ Q \end{bmatrix}$$

#### 2.2. Mathematical Model

Consider integer variables x<sub>ii</sub> which indicate whether a vehicle goes from node i to node j or not, and additional continuous variables  $u_i$  for  $i \in V \setminus \{0\}$  that represent the load of the vehicle after visiting customer i. The mathematical model of the problem is:

$$\mathbf{Min} \ \sum_{i \in V} \sum_{j \in V} c_{ij} x_{ij} \tag{1}$$



Subject to

$$\sum_{i \in V} x_{ij} = 1 \qquad j \in V \setminus \{0\}$$
 (2)

$$\sum_{j \in V} x_{ij} = 1 \qquad i \in V \setminus \{0\}$$
 (3)

$$\sum_{i\in V} x_{i0} = m \tag{4}$$

$$\sum_{i \in V} x_{0j} = m \tag{5}$$

$$u_i - u_j + Qx_{ij} \le Q - q_j$$
  
 $i, j \in V \setminus \{0\}, i \ne j, q_i + q_i \le Q$  (6)

$$q_i \le u_i \le Q$$
  $i \in V \setminus \{0\}$  (7)

$$x_{ij} \in \{0,1\}$$
  $i, j \in V$  (8)

The objective function given in (1) states that costs should be minimized. Constraint (2) states that for each node, excluding node 0, there can only be a single outgoing arc to any other node, while constraint (3) states that there can only be a single incoming arc to a node from any other node, excluding note 0. Therefore, the first two constraints (2) and (3), force that a single vehicle goes into and out of every node. Constraint (4) and (5) ensure that a total of m vehicles leave the depot and then return to it. Constraints (6) and (7) are sub-tour elimination constraints imposing both the capacity and connectivity reguirements of ACVRP.

Since the ACVRP is known to be NPhard combinatorial optimization problem, the time it takes to solve the problem is grow exponentially as the number of asstomers increases. In other words, the exact algorithms can only solve relatively small problems. On the contrary, a heuristic is a solution strategy that produces an answer without any formal guarantee as to the quality. Heuristics clearly are methods which produce good solutions in practice but do not guarantee optimality. Therefore, in the next section a relatively simple heuristic algorithm is developed to obtain a quick solution for a large problem.

#### 3. HEURISTIC FOR ACVRP

Classical VRP heuristics can be broadly classified into three categories: constructive heuristics, the two-phase heuristes, and the improvement methods. In the two-phase heuristics, the problem is decomposed into its two natural components i.e., clustering of nodes into feasible routes and actual route construction, with possible feedback loops between the two stages. The two-phase heuristics are divided into two classes: cluster first route second methods and route first cluster second methods. In the first case, nodes are first organized into feasible clusters, and a vehicle route is constructed for each of them. In the second case, a tour is first built on all nodes and is then segmented into feasible vehicle

When finding an initial solution to a routing problem, the initialization criteria refers to the process of finding the first node to insert into a rate, which is referred to as the seed node. Because of the strong influence of the seeds in the assignment of nodes to routes, and therefore on the final solution obtained, the choice of the seeds is a very critical step in applying cluster first second methods. To avoid unpredictable results led by the seed selection, the heuristic developes in this paper is based on the idea of route first cluster second methods instead of cluster first route second methods, which are more extensively used.

The proposed heuristic for ACVRP consists of three steps: creating initial route, grouping customers, and building final feasible route for each group of customers obtained in the second step.

#### **Creating Initial Route** 3.1.

Generate a traveling salesman tour on all customers without considering the capacity constraint of the vehicles. In this paper, the initial route will be done using two simple procedures. The first procedure is the well-known Nearest Neighbor Algorithm (NNA), which can be used both for the asymmetric and the symmetric instances.

The procedure of *NNA* is as follows:

- 1. Select the depot as a starting node and insert the node closest to it
- 2. Iteratively insert the node closest to the last node inserted until no more node is available

# Connect the last node inserted with the depot

The second procedure is specially proposed for the asymmetric problem. In this paper, the initial route will be created using a modified procedure of the well-known Johnson's Algorithm for n-jobs two machines problem (Johnson, 1974). In this proposed procedure, all the nodes on the graph, except the depot, are sequenced as follows:

- 1. Let  $d_{0i}$  be the distance from depot to node i and  $d_{i0}$  be the distance from node i to depot (  $i \in V \setminus \{0\}$ )
- 2. List the  $d_{0i}$  and  $d_{i0}$  on a separate two columns
- 3. For every node  $i \in V$  find the minimum distance of the two columns. If this minimum distance found on the  $d_{0i}$  column, assign the corresponding node to the first available place in the sequence. Otherwise, assign the node to the last available place in the sequence. Remove this node from the list of nodes to be sequenced. Ties are resolved by randomly choosing either position in the sequence for the assignment.
- 4. Repeat the process until all nodes have been sequenced.
- Connect the first and the last nodes of the sequence with the depot.

#### 3.1. Grouping Customers

The feasibility of the route will not depend on the sequence the customers are visited in, but rather depends on the set of customers assigned to the vehicle, i.e. the delivery of the route does not exceed the vehicle's capacity. Therefore, the initial route obtained from the previous step is then divided into a number of routes that satisfies capacity constraint. It is assumed that the number of available vehicles is at least the same as the number of routes obtained.

#### 3.2. Building Final Routes

For each group of customers obtained in the second step, find a tour of minimal distance that visits all nodes exactly once, starting and ending at the depot. Since this step is actually solving the *Traveling Salesman Problem* for each group of

customer, it can be performed by any heuristic or exact method. Nevertheless, in this paper it will performed by the *Nearest Neighbor Algorithm*.

#### 4. NUMERICAL EXAMPLE

Consider an ACVRP where a depot has to serve nine customers. The distances between points are shown in Table 1 and the demand at each customer is shown in Table 2. Let the capacity of the available vehicles is equal to 23.

Table 1. Distance matrix

From \To	Depot	1	2	3	4	5	6	7	8	9
Depot	0	10	3	6	9	5	7	8	2	4
1	5	0	5	4	2	3	6	10	7	8
<u> </u>	-	_	_	-		_	-	_		_
2	4	9	0	7	8	6	5	2	4	3
3	7	1	3	0	4	8	9	10	5	2
4	3	2	6	5	0	7	4	8	9	3
5	2	7	2	7	5	0	5	6	4	10
6	5	6	9	6	6	3	0	7	5	7
7	6	4	8	4	7	4	8	0	3	8
8	4	3	4	7	8	5	5	4	0	5
9	3	5	5	3	4	6	6	5	7	0

Table 2. Demand at each customer

Customer	1	2	3	4	5	6	7	8	9
Demand	4	6	5	4	7	3	5	4	4

If the *NNA* is assigned to create the initial route, the result will be such as follows:

Since the total demand of all customers is 42 and the vehicle capacity is 23, there will be two routes to determine in the next step. The first route will involves the group of customers 8, 1, 4, 9, and 3 with the total delivery of 21 and the second route will involves the group of customers 2, 7, 5, and 6 with the total delivery of 21 also.

The last step is to reassign the *NNA* to build the final tour for each of the customers group. The matrix distance for the first and the second group of customers is shown in Table 3 and Table 4, respectively.

Table 3. Distance matrix for group 1									
From \ To	Depot	8	1	4	9	3			
Depot	0	2	10	9	4	6			
8	4	0	3	8	5	7			
1	5	7	0	2	8	4			
4	3	9	2	0	3	5			
9	3	7	5	4	0	3			
3	7	5	1	4	2	0			

Table 4. Distance matrix for group 2

From \ To	Depot	2	7	5	6
Depot	0	3	8	5	7
2	4	0	2	6	5
7	6	8	0	4	8
5	2	2	6	0	5
6	5	9	7	3	0

The final route obtained from the third step for the first group is:

Depot - 8 - 1 - 4 - 9 - 3 - Depot with the total travel distance of 20, while for the second group is:

Depot - 2 - 7 - 5 - 6 - Depot with the total travel distance of 19.

To give more illustration of how the proposed algorithm works, suppose the vehicles capacity is 16 instead of 23. The solution will consists of three final routes, they are:

- Depot 8 1 4 9 Depot, with the total delivery of 16 and the total distance of 13 in the first group,
- Depot 2 7 3 Depot, with the total delivery of 16 and the total distance of 16 in the second group, and
- Depot 5 6 Depot, with the total delivery of 10 and the total distance of 15 in the third group.

In what follows, the same problem will be solved using the modified *Johnson's Algorithm* in the step of creating the initial route. The distance from depot to each node and from each node to depot is listed in Table 5 below.

Table 5. List of the distance

i	d <sub>oi</sub>	d <sub>i0</sub>	i	d <sub>0i</sub>	d <sub>i0</sub>
1	10	5	6	7	5
2	3	4	7	8	6
3	6	7	8	2	4
4	9	3	9	4	3
5	5	2			

The initial route is then Depot - 8 - 2 - 3 - 7 - 1 - 6 - 4 - 9 - 5 - Depot.

If the vehicle capacity is 23 then the first route will involves customers 8, 2, 3 and 7, with the total delivery of 20, and the second route will involves customers 1, 6, 4, 9, and 5, with the total delivery of 22.

Using the *NNA* in the last step, the resulted final routes are:

Depot - 8 - 2 - 7 - 3 - Depot with the total travel distance of 19 in the first group, and

 $\overline{Depot} - 9 - 4 - 1 - 5 - 6 - Depot$  with the total travel distance of 23 in the second group.

If the vehicle capacity is 16 then the three final routes are:

- Depot 8 2 3 Depot, with the total delivery of 15 and the total distance of 20 in the first group,
- Depot 6 1 7 Depot, with the total delivery of 12 and the total distance of 29 in the second group, and
- Depot 9 4 5 Depot, with the total delivery of 15 and the total distance of 17 in the third group.

The results for this example show that the final routes obtained are better when the NNA applied in the first step, than those when the modified Johnson's Algorithm applied. It can be easily accepted, since the quality of the final routes is strongly depends on the quality of the initial route. All the distance from one customer point to another are considered in building the initial route by NNA, while the modified Johnson's Algorithm only considering the distance from depot to each customer point and the inverse distance.

#### 4. CONCLUSION

In this paper, a variant of Capacitated Vehicle Routing Problem in which the distance matrix is asymmetric is considered. Despite the fact that this type of problem were much less studied in the literature, asymmetric models are relevant



to a wider range of applications, and more general then symmetric models. In this study, the problem was formulated as an *Integer Linear Program* and a heuristic algorithm based on the *route first cluster second* method is developed.

The proposed heuristic consists of three steps, i.e. creating the initial route, grouping the customers, and building the final routes. The Nearest Neighbor Algorithm and the modified Johnson's Algorithm are then proposed to apply in the first step. While the Nearest Neighbor Algorithm can be applied for both asymmetric and symmetric instances, the proposed modified Johnson's Algorithm can only be applied for asymmetric instances.

This study can be extended in several directions. For instance, it might need to consider cases when the vehicle's capacity is not the only restriction imposed, as found in many variants of VRP.

#### 5. REFERENCES

- (a) Baldacci, R., Hadjiconstantinou E. and A. Mingozzi, (2004), "An exact algorithm for the capacitated vehicle routing problem based on a twocommodity network flow formulation," Operations Research 52, pp. 723-738.
- (b) Fischetti M., Toth P, and D. Vigo, (1994), "A Branch-And-Bound Algorithm for the Capacitated Vehicle Routing Problem on Directed Graphs," Operations Research, 42 (5), pp. 846-859.
- (c) Fukasawa, R., Longo, H., Lysgaard, J., Poggi, D.M., Reis, M., Uchoa, E. and R. F. Werneck, (2006). "Robust branch-and-cut-and-price for the capacitated vehicle routing problem," *Mathematical Programming Series*, 106, 2006, pp. 491–511.
- (d) Gendreau, M, Laporte, G and Jean-Yves Potvin, (2002), "Metaheuristics for the capacitated vrp," In: P. Toth and D. Vigo, editors, The Vehicle Routing Problem, SIAM Monographs on Discrete Mathematics and Applications, SIAM, pp. 129-154.

- (e) Johnson, L.A. and D.C. Montgomery, (1974), "Operations research in production planning, scheduling, and inventory control," John Wiley & Sons Inc., New York.
- (f) Laporte, G., Mercure, H. and Y. Nobert, (1986), "An exact algoritm for the asymmetrical capacitated vehicle routing problem," *Networks*, 16, 1986, pp. 33-46.
- (g) Laporte, G. and Frédéric Semet, (2002), "Classical heuristics for the capacitated vrp," In: P. Toth and D. Vigo, editors, The Vehicle Routing Problem, SIAM Monographs on Discrete Mathematics and Applications, SIAM, pp. 109-128.
- (h) Lysgaard, J, Letchford, A.N. and Richard W. Eglese, (2004), "A new branch-and-cut algorithm for the capacitated vehicle routing problem," *Mathematical Programming, Series A*, 100, pp. 423–445.
- (i) Ralphs, T.K., Kopman, L., Pulleyblank, W.R. and L. E. Trotter, (2003), "On the capacitated vehicle routing problem," *Mathematical Programming Series* B, 94, pp. 343-359.
- (j) Toth, P. and D. Vigo, (2002), "An overview of vehicle routing problems," In: P. Toth and D. Vigo, editors, The Vehicle Routing Problem, SIAM Monographs on Discrete Mathematics and Applications, SIAM, pp. 1-26.
- (k) Toth, P. and D. Vigo, (2002), "Models, relaxations and exact approaches for the capacitated vehicle routing problem," Discrete Applied Mathematics 123, pp. 487-512.
- Vigo, D., (1996). "A heuristic algorithm for the asymmetric capacitated vehicle routing problem," European Journal of Operational Research, 89, pp. 108-126.

#### **AUTHOR BIOGRAPHIES**

**Tjutju T. Dimyati** is a lecturer in Industrial Engineering Department of Pasundan University, Bandung. She received her

ISSN: 1978-774X

degree of Doctoral in Industrial Engineering from The Institute Technology Bandung in 2004. Her research interests are in the area of Operations Research, Logistics Planning, and Production Planning and Inventory Control. Currently she is doing research in the area of Organizational Culture as well.

# HEURISTIC FOR ASYMMETRIC CAPACITATED VEHICLE ROUTING PROBLEM

PRC	BLEM		
ORIGINA	ALITY REPORT		
	5% 26% INTERNET SOURCES	18% PUBLICATIONS	10% STUDENT PAPERS
PRIMAR	Y SOURCES		
1	www.slideshare.net Internet Source		5%
2	id.123dok.com Internet Source		4%
3	research-report.umm.ac	c.id	2%
4	mts.intechopen.com Internet Source		2%
5	dosen.univpancasila.ac.i	id	2%
6	rdrohmat.staff.telkomur	niversity.ac.id	2%
7	scholarbank.nus.edu.sg		1 %
8	Daniele Vigo. "A heuristi asymmetric capacitated problem", European Jou Research, 1996	vehicle routing	<b>I</b> %

Publication

9	epdf.pub Internet Source	1 %
10	hdl.handle.net Internet Source	1 %
11	bibing.us.es Internet Source	1 %
12	repository.gunadarma.ac.id Internet Source	1 %
13	citeseerx.ist.psu.edu Internet Source	1 %
14	repo.unand.ac.id Internet Source	1 %
15	www.orssa.org.za Internet Source	1 %
16	eprints.eemcs.utwente.nl Internet Source	1 %

Exclude quotes On Exclude bibliography On Exclude matches < 1%